

DYNASOLVE M-10

Dynasolve M-10 is an excellent product for removing uncured silicones, silicone oils, and silicone-based mold release agents.

General

Dynasolve M-10 is an essentially odorless, high purity, high boiling point solvent. It is an excellent flushing agent for removing uncured silicone from application and dispensing equipment. Dynasolve M-10 is also a great product for removing silicone residue from parts that need to be cleaned prior to further processing, such as painting.

Applications

1. Removal of silicone oils.
2. Removal of silicone-based mold release agents.
3. Removal of most silicone residue from almost any surface.
4. Flushing of uncured silicone and silicone foam from dispensing equipment.
5. For removal of cured RTV silicones and silicone coatings, try Dynasolve 210, 218, 220, 225, or 230.

Specifications

Color:	Clear
Specific Gravity:	0.79
Boiling Point:	>400°F
Flash Point:	160°F (PMCC)

Directions For Use

1. Pour Dynasolve M-10 into a steel or polypropylene container.
2. Immerse part to be cleaned in Dynasolve M-10 at room temperature.
3. If silicone is not removed at room temperature, heat to 150°F.
4. Remove and rinse part with alcohol or water.
5. For flushing, use as you would any flushing agent.

Caution and Warnings

Dynasolve M-10 contains powerful organic solvents. It is harmful if inhaled or swallowed. Avoid breathing vapors or mist. Keep away from heat and flame. Avoid contact with eyes and skin. Wear gloves, safety goggles, and protective clothing when handling. Use with adequate ventilation. Refer to MSDS before use, for disposal, or additional safe handling.